

CONNECTIVITY							
MODEL	DESCRIPTION	VOLTAGE	OUTPUT				
MM100s	MediaMaster Source Unit	14.4v DC	4 stereo pairs of RCA plugs (3 variable + 1 fixed)				
MMR-20	Round Wired Remote						
MMR-10W	Wireless Remote						
MBT-CRX	Bluetooth Audio Controller & Receiver	8v-28v DC	Stereo RCA				
MBT-RX	Bluetooth Audio Receiver	8v-28v DC	Stereo RCA				
ACCESSORIES							
MMC-6	Remote Cable for MMR-20	1.83m					
MMC-25	Remote Cable for MMR-20	7.62m					
MMC-2Y	Remote Cable Y-Splitter for MMC-6 & MMC-25						
SPEAKERS							
MODEL	DESCRIPTION	DIAMETER	MOUNTING DEPTH	RMS POWER	IMPEDANCE	GRILL OPTIONS	COLOUR OPTIONS
MX770-CCX	Cockpit Coaxial Speaker	195mm	80mm	25W - 150W	4Ω (Ohms)	Classic or Sports	White or Titanium/Black
MX650-CCX	Cockpit Coaxial Speaker	165mm	70mm	15W - 100W	4Ω	Classic or Sports	White or Titanium/Black
M880-CCX	Cockpit Coaxial Speaker	224mm	132mm	50W - 250W	4Ω	Classic or Sports	White or Titanium/Black
M770-CCX	Cockpit Coaxial Speaker	195mm	80mm	40W - 170W	4Ω	Classic or Sports	White or Titanium/Black
M770-TCX	Tower Coaxial Speaker	195mm	80mm	40W - 175W	4Ω	Classic or Sports	White or Titanium/Black
M650-CCX	Cockpit Coaxial Speaker	165mm	75mm	25W - 150W	4Ω	Classic or Sports	White or Titanium/Black
M770-CCS	Cockpit Component Speaker	195mm	80mm	40W - 170W	4Ω	Classic or Sports	White or Titanium/Black
M770-TCS	Tower Component System	195mm	80mm	40W - 175W	4Ω	Classic or Sports	White or Titanium/Black
TWEETERS							
MODEL	DESCRIPTION	DIAMETER	MOUNTING	RMS POWER	IMPEDANCE	GRILL OPTIONS	COLOUR OPTIONS
M100-CT	Component Tweeter Set	100mm	Included	40W - 175W	4Ω	Classic or Sports	White or Titanium/Black
ETX SPEAKERS							
MODEL	DESCRIPTION	DIAMETER	MOUNTING	RMS POWER	IMPEDANCE	GRILL OPTIONS	COLOUR OPTIONS
M880-ETXv3	Enclosed Tower Coaxial Speaker	224mm	376mm	50W - 250W	4Ω	Classic or Sports	White or Titanium/Black
M770-ETXv3	Enclosed Tower Coaxial Speaker	195mm	318mm	40W - 175W	4Ω	Classic or Sports	White or Titanium/Black
MX770-ETXv3	Enclosed Tower Coaxial Speaker	195mm	318mm	25W - 150W	4Ω	Classic or Sports	White or Titanium/Black
ETX SPEAKER CLAMPS							
MODEL	DESCRIPTION	DIAMETER	APPLICATION				
MCPv3-XXX	Enclosed Tower Speaker Clamp	33.4–63.5mm	Universal pipe fitting				
MCPv3-MC	Enclosed Tower Speaker Clamp	Custom	Mastercraft Specific				
MCPv3-NC	Enclosed Tower Speaker Clamp	Custom	Nautique Specific				
MCPv3-DM	Enclosed Tower Speaker Clamp	Universal	Deck Mount				
MCPv3-SM	Enclosed Tower Speaker Clamp	Universal	Surface Mount				

Recommended RMS Amplifier Power for Subwoofer Drivers: This is the RMS amplifier power recommended by JL Audio for each driver. Choosing a good quality amplifier in this power range will make use of the woofer's low-distortion performance envelope, without undue risk of failure. Use of less than the recommended power range may not damage the woofer, but may result in unsatisfactory performance. Caution must be exercised when using amplifiers that approach or meet the maximum recommended power. Use of an amplifier that exceeds the driver's "Continuous Power Handling (Pt)" specification voids the warranty.

Recommended RMS Amplifier Power for Full-Range Speakers (Components and Coaxials): This is the RMS amplifier power recommended by JL Audio for each speaker system (per channel). A properly set, good quality amplifier in this power range will produce clean, dynamic audio without undue risk of failure when listening to music. Failure to set the amplifier's input sensitivity correctly will compromise reliability. Use of less than the recommended power range will not damage the speakers, but may result in unsatisfactory performance. Use of more power than recommended will compromise reliability with aggressive use and will void the warranty.

PRODUCT SPECIFICATION

SUBWOOFERS							
MODEL	DESCRIPTION	DIAMETER	MOUNTING	RMS POWER	IMPEDANCE	GRILL OPTIONS	COLOUR OPTIONS
M10W5	Subwoofer Driver	250mm	151mm	75W - 250W	4Ω	Classic or Sports	White or Titanium/Black
M10IB5	Subwoofer Driver - Infinite Baffle	250mm	151mm	75W - 250W	4Ω	Classic or Sports	White or Titanium/Black
M8IB5	Subwoofer Driver - Infinite Baffle	200mm	132mm	50W - 200W	4Ω	Classic or Sports	White or Titanium/Black
MX10IB3	Subwoofer Driver - Infinite Baffle	250mm	128mm	55W - 175W	4Ω	Classic or Sports	White or Titanium/Black

MHD 12v AMPLIFIERS				
MODEL	DESCRIPTION	CHANNELS	DIMENSIONS	CONTINUOUS POWER (RMS METHOD)
MHD900/5	900W HD Amp	5	49 x 273 x 211mm	100W x 5 + 500W x 1 @ 4Ω per ch. / 75W x 4 + 500W x 1 @ 2Ω per ch.
MHD750/1	750W HD Amp	1	49 x 273 x 211mm	750W x 1 @ 1.5-4Ω
MHD600/4	600W HD Amp	4	49 x 273 x 211mm	150W x 4 @ 1.5-4Ω / 300W x 2 @ 3 - 8Ω

ACCESSORIES			
HD-RLC	Remote Bass Control		5.5m cable

MHD 24v AMPLIFIERS				
MHD900/5-24v	900W HD Amp	5	49 x 273 x 211mm	100W x 5 + 500W x 1 @ 4Ω / 75W x 4 + 500W x 1 @ 2Ω
MHD600/4-24v	600W HD Amp	4	49 x 273 x 211mm	150W x 4 @ 1.5-4Ω / 300W x 2 @ 3-8Ω

ACCESSORIES			
HD-RLC	Remote Bass Control		5.5m cable

M 12v AMPLIFIERS				
M200/2	200W Class D Amplifier	2	52 x 174 x 180mm	75W x 2 @ 4Ω / 100W x 2 @ 2Ω / Bridged: 200W x 1 @ 4Ω
M400/4	400W Class D Amplifier	4	52 x 216 x 180mm	75W x 4 @ 4Ω / 100W x 4 @ 2Ω / Bridged: 150W x 2 @ 8Ω / Bridged: 200W x 2 @ 4Ω
M500/3	500W Class D Amplifier	3	52 x 216 x 180mm	75W x 2 + 180W x 1 @ 4Ω / 100W x 2 + 300W x 1 @ 2Ω / Bridged: 200W x 1 @ 4Ω
M600/1	600W Class D Amplifier	1	52 x 216 x 180mm	400W x 1 @ 4Ω / 600W x 1 @ 2Ω
M600/6	600W Class D Amplifier	6	52 x 260 x 180mm	75W x 6 @ 4Ω / 100W x 6 @ 2Ω / Bridged: 150W x 3 @ 8Ω / Bridged: 200W x 3 @ 4Ω
M700/5	700W Class D Amplifier	5	52 x 260 x 180mm	75W x 4 + 180W x 1 @ 4Ω / 100W x 4 + 300W x 1 @ 2Ω / Bridged: 200W x 2 @ 4Ω
M800/8v2	800W Class D Amplifier	8	52 x 374 x 180mm	75W x 8 @ 4Ω / 100W x 8 @ 2Ω / Bridged: 200W x 4 @ 4Ω
M1000/5v2	1000w Class D Amplifier	5	52 x 374 x 180mm	75W x 4 + 400W x 1 @ 4Ω / 100W x 4 + 600W x 1 @ 2Ω / Bridged: 200W x 2 @ 4Ω

ACCESSORIES			
HD-RLC	Remote Bass Control		5.5m cable

M 24v AMPLIFIERS				
M400/4-24v	400W Class D Amplifier	4	52 x 216 x 180mm	75W x 4 @ 4Ω / 100W x 4 @ 2Ω / Bridged: 150W x 2 @ 8Ω / Bridged: 200W x 2 @ 4Ω
M600/6-24v	600W Class D Amplifier	6	52 x 260 x 180mm	75W x 6 @ 4Ω / 100W x 6 @ 2Ω / Bridged: 150W x 3 @ 8Ω / Bridged: 200W x 3 @ 4Ω
M800/8v2-24v	800W Class D Amplifier	8	52 x 374 x 180mm	75W x 8 @ 4Ω / 100W x 8 @ 2Ω / Bridged: 200W x 4 @ 4Ω

ACCESSORIES			
HD-RLC	Remote Bass Control		5.5m cable

MX 12v AMPLIFIERS				
MX500/4	Class D Full-Range Amp	4	45 x 237 x 115mm	125 W x 4 @ 2 Ω / 70 W x 4 @ 4 Ω - 14.4V
MX500/1	Class D Wide-Range Amp	4	45 x 237 x 115mm	500 W x 1 @ 2 Ω / 300 W x 1 @ 4 Ω - 14.4V
MX300/1	Class D Wide-Range Amp	4	45 x 220 x 78.5mm	300 W x 1 @ 2 Ω / 160 W x 1 @ 4 Ω - 14.4V
MX280/4	Class D Full-Range Amp	4	45 x 220 x 78.5mm	70 W x 4 @ 2 Ω / 50 W x 4 @ 4 Ω - 14.4V

ACCESSORIES			
M-RBC-1	Remote Bass Control		5m cable